iaguar com		1
jaquar.com		BATH + LIGHT
Document No. SNW/ITS/24/955P180PP		
5100/115/24/3551 18000		
	T.T. sugar	(SED)
	580	Ø58Ø100
	40	f
f Ø15		
L0	8 7 +145	
	<u>40</u>	
TOP VIEW	SIDE VIEW	BACK VIEW
	SIDE VIEW	BACKVIEW
General Information		
Product Code	ITS-WHT-15955P180PP	
Brand	Jaquar	
Colour	White	
Туре	Back To Wall WC - P TRAP	
Material	Ceramic-Vitreous China (VC)	
Product Specification Product Dimension	370x580x430 mm	
Bowl Opening (Inner Dimension)	260x335 mm	
Product Net Weight	29.0 kg.	
Product Gross Weight	32.5 kg	
Packaging Dimension Outlet	600x440x450 mm Horizontal	
Trap Distance	P Trap - 180 mm	
Inlet And Outlet Hole Dimension	Internal diameter of inlet hole dia. $Ø$ 58 ± 3 mm	
	External diameter of outlet hole dia. Ø 100 ± 5 mm 1. Back to wall WC, 2. Rimless 3.Anti bacterial Glaze	
	4.Dual Flush-3/6 LPF Intelligent Seat with following features:	
	1. Adjustable seat temperature - 33/37°c 2. Adjustable water temperature - 35/38°c	
Product Features	. Adjustable air temperature - 33/38/43°c	
Product reatures	Anti-bacterial seat/nozzle/ceramic 5. LED night light 6. Air dryer 7. Front & rear wash nozzle	
8. Adjustable water pressure 9. Instant heating technology		
	10. Self-cleaning 11. Water massage cleaning	
ACCESSORIES PROVIDED		
Electronic PP Seat cover	ITS-WHT-89107	
Inlet outlet Gasket	ZPS-WHT-GK01	
Fixing kit	ZPS-SNS-FB02	
ACCESSORIES RECOMMENDATION		
Concealed cistern JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS		
CARE AND CLEANING GUIDELINES		
¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.		
¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.		
– Carefully inspect the new product for damage before installation.		
¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.		
¬ Risk of external leakage. Do not lift or rock the bowl after placement.		
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.		
¬ Do not allow cleaners to sit or soak on the product.		
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.		
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.		
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.		
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.		
QUALITY MANAGEMENT SYSTEM - ISO 9001		
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product		
Prepared by Manash Leve	Checked by	Approved by