Bourner No. SWW/DS/24/083 WW	jaquar.com			JAQUAT BATH+LIGHT	
And Provide State Stat			-		
Product Case Marce Server Marce Serv	SNW/OPS/24/603		- •		
Provide the set of the se					
Provide the set of the se					
Provide the set of the se					
Provide the set of the se	·				
before the set of		<u>410</u>			
being and a second		G ⊕ _ Ø35 E	610	470	
			⁵²⁰	<u> </u>	
	6	-782 / € −	8-95-1 -95-1		
LOP VEW Lot VIII General Information INSERVIT-35003 General Information IRREV Color Vite VIII-35003 Golar Vite VIIII STATE Color Vite VIIII STATE Color Contract top basin Mater Specification Contract top basin Mater Specification Stot A700 Trans Vite VIIII STATE Stot A700 Trans Statistication Stot A700 Trans Vite VIIII STATE Stot A700 Trans Vite VIIII S	Ø45				
IDENTIFY IDENTIFY Resear Information IDENTIFY Resear Information IDENTIFY Resear Information IDENTIFY Resear Information IDENTIFY Color White Color White Color Contract top basin Material IDENTIFY Contract top basin Material IDENTIFY Contract top basin Material IDENTIFY IDENTIFY Reduct IDENTIFY IDENTIFY					
General Information Product Code US-WHT-35033 Brand Jaquar Colur While Colur While Type Counter top basin Type Counter top basin While Counter top basin Type Counter top basin Material Counter top basin Product Section 4004704210 mm. Basin inner Dimension 4004704210 mm. Basin inner Dimension 400470420 mm. Reclarging Linemander 11 %. Product Section Weight 11 %. Reclarging Linemand Yes Section Manual Counter Reclarging Linemand Yes Section Manual Counter Reclarging Linemand Yes Section Manual Counter top Basin Type Inde Line Xes Type Inde Line Xes Section Manual Counter top Basin Reclarging Linemand Counter top Basin Type Inde Line Xes Section Manual Counter top Basin Reclarging Linemand Counter top Basin Type Inde Line Xes Section Manual Counter top Basin Reclarging Linemand Counter top Basin Type Inde Line Xes Section Manual Counter top Basin Reclarging Linema	T		BACK VIEW	SIDE VIEW	
Product Code KUS WHT 35603 Brand Jaquar Collour While Colour While Colour While Material Ceramic-Vitreous China (VC) Product Specification Forduct Tomeson Status Tome Tomeson Status 70b.170 mm Basin non-rolmension Status 70b.170 mm Product free Weight 11 kg. Product Tores Weight 12 kg. Product Reatures Tap hole and out-flow for all all status for data. 49b s 12/-1 mm Horizontial distance between the centre line of the tap hole and the centre line of the waste outliet hole \$200 mm Product Reatures Product Reatures Product Reatures Tap hole and over flow hole and the centre line of the tap hole and the centre line of the waste outliet hole \$200 mm Product Reatures Installation Template Deerflow hole Cap Pro-Withole Cap Zirs-WHT-90					
anand Aquar Golour White Golour Contert top basin Material Ceramic-Vitreous China (VC) Product Specification From Contern (VT) (VC) Product Specification Stable 700 k170 min Basin Inter Dimension Stable 700 min Product Specification Product Specification Product Specification Stable 700 min Basin Inter Dimension Stable 700 min Product Reatures Tap hole Basin Stable 700 min Product Reatures Tap hole Basin Stable 700 min Rectangular counter top Basin Product Reatures Product Reatures Tap hole Basin Papele Outfort Notice Product Reatures Product Reatures Tap hole Basin Papele Outfore AntO CLEANING GOULES Tore Antige Reating Ballion Antige Reating					
olsow White Open A Counter top basin Type A Counter top basin Reternal D Counter top basin Product Spectration Product Spectration Product Spectration Spectration Tap Hole And Outlet Hole Dire Spectration Spectration Tap Hole And Outlet Hole Dire Spectration Spectration Product Spectration Spectration Spectration Spectration Product Spectration Spectration Product Spectration Spectration Product Spectration Spectration Product Spectration Spectration </td <td>Product Code</td> <td>KUS-WHT-35603</td> <td></td> <td></td>	Product Code	KUS-WHT-35603			
Type Counter top basin Material ceramic Vitreous Ohna (VC) Product Specification Forduct Specification Product Specification 610x470x170 nm Basin none Vitrenson 450x28x115 nm Product Net Weight 11 kg. Product Kerwise Weight 12 kg. Packaging Dimension 652x480x200 nm Outlet Vertical Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole (al., 45 ± 2/.1 mm Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole (al., 45 ± 2/.1 mm Product Teatures Rectangular counter top Basin Tap hole and over flow hole Ant germ gaze Accessofters includeE Zers WH100x10x10x10x10x10x10x10x10x10x10x10x10x	Brand	Jaquar			
Material Ceramic-Vitreous China (VC) Product Specification Forduct Dimension 6100-4720x170 nm Basin Inner Dimension 450x25x115 mm Forduct Dimension 450x25x115 mm Product Merker Weight 11 kg. Forduct Chinas Weight 12 kg. Packaging Dimension 625x480x200 mm Gold How Step (Step (Colour	White			
Product Specification Product Specification Product Dimension 60.450/20350.115 mm Product Net Weight 11 kg. Product Cross Weight 12 kg. Product Cross Weight 13 kg. Product Cross Weight 14 kg. Product Cross Weight 15 kg. Product Cross Weight 16 kg. Product Cross Weight 17 ap hole dia. Ø 35 ± 2 mm Product Net Weight 18 hole dia. Ø 35 ± 2 mm Product Cross Weight 18 hole dia. Ø 35 ± 2 mm Product Cross Weight 19 hole dia. Ø 35 ± 2 mm Product Creatures 10 hole and the centre line of the vaste outlet hole § 200 mm Product Features 17 ap hole and ver flow hole 18 hole And Outlet Hole Dimension 18 her And Cross Weight 19 hole And Outlet Hole Dimension 19 hole and ver flow hole 19 hole and the centre line of the vaste outlet hole § 200 mm Product Features 10 hole and ver flow hole 10 hole and the centre line of the vaste outlet hole § 200 mm Product Features 10 hole Cross Weight 10 hole and ver flow hole 20 hole	Туре	Counter top basin			
Product Dimension 610x470x170 mm Basin Inner Dimension 660x25x115 mm Product RE Weight 11 kg. Product RE Weight 12 kg. Product Gross Weight 22 kg. Packaging Dimension 625x480x200 mm Outlet Vertical Tap hole dia. Ø 35 ± 2 mm Tap hole dia. Ø 35 ± 2 mm Tap hole And Outlet Hole Dimension Insernal diameter of outlet hole dia. Ø45 ± 2/-1 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole < 200 mm	Material	Ceramic-Vitreous China (VC)			
Basin Inner Dimension 460/285/115 mm Product Net Weight 11 kg. Product Kress Weight 12 kg. Packaging Dimension 625/x480x200 mm Outlet Vertical Tap hole And Outlet Hole Dimension Fap hole dia. Ø 35 ± 2 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole ≤ 200 mm Product Features Rectangular counter top Basin Tap hole and over How hole Anti germ glaze Accessores include Installation Template Overflow hole Cap 25-WHT-9012B CARE AND CLEANING GUIDEUNES Installation Template – Vitreous chine sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. – The product is neavy and it is recommended that two persons hold it while it is being fixed. – Carefully inspect the new product for damage before installation. — Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. — Nisk of product and sing to roack on the product. – Ube a soft, damage over tight to cale. Never use abrasive material like a bristle brush or scouring pad. – Ube a soft, damage over tight to native immediately after applying it caners. – Ube a soft, damage over tight	Product Specification				
Product Net Weight 11 kg. Product Gross Weight 12 kg. Tap hole data Ø 35 ± 2 mm Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia: Ø45 ± 2/1 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole ≤ 200 mm Rectangular content to D Basin Product Features Product Features Rectangular content to De Basin Product Features Rectangular content to De Basin Product Features Rectangular content to De Basin Product Gross Weight 12 kg. CRE AND CLEANING GUIDEUNES CRE AND CLEANING GUIDEUNES	Product Dimension				
Product Gross Weight 12 kg. Packaging Dimension 625x80200 mm Outlet Vertical Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø 35 ± 2 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole \$ 200 mm Product Features Retrangular counter top Basin Tap Hole And Outlet Hole Dimension Product Features Retrangular counter top Basin Tap hole and over flow hole Anti germ glaze Accessores INCLUDED Instillation Template Overflow hole Cap 2PS-WHT-90128 CARE AND CLEANING GUIDELINES Product for damage before installation.					
Packaging Dimension 625:x480.200 mm Outlet Vertical Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø 35 ± 2 mm Product Features Tap hole and 0x5 ± 2 mm Product Features Rectangular counter top Basin Tap hole and over flow hole Anti germ glaze Accessories includeD Installation Template Overflow hole Cap ZPS-WHT-90128 CARE AND CLEANING GUIDELING Installation Template Overflow hole Cap ZPS-WHT-90128 Care And CLEANING GUIDELING Installation Template - Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use threaster. - The product fis heavy and it is recommended that two persons hold it while it is being fixed. - Carefully inspect the new product for damage before installation. - Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. - Niks of strange before installation. - Niks of and uceanies to sit to soak on the product. - Do not allow cleaners to sit to soak on the product. - Uber avaitard cleaning solution on an inconspicuous are and on the otex solut in socal on the product. - Ubes a soft, damagee doponge or cloh to clean. Never use abrasive mat	-				
Outed Vertical Tap hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø45 + 2/-1 mm Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø45 + 2/-1 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole 5 200 mm Product Features Rectangular counter top Basin Tap hole and over flow hole Antigering Baze Accessories includeD Tap hole and over flow hole CARE AND CLEANING GUIDEDLINES Installation Template Overflow hole Cap ZPS-WHT-90128 Carefully inspect the new product for damage before installation. -					
Tap Hole And Outlet Hole Dimension Tap hole dia. Ø 35 ± 2 mm Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø 45 + 2/.1 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole ≤ 200 mm Product Features Restangular counter top Basin Tap hole and over flow hole Anti germ glaze Accessories includeD Installation Template Overflow hole Cap ZPS-WHT-90128 CARE AND CLEANING GUIDELING Installation Template and over flow hole Antiger mglaze ~ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. ~ Vitreous china sanitary ware products or damage before installation. Rest of product damage. Over tightening may cause breakage or chipping of vitreous china. ~ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement. ~ Always test your cleaning solution on an inconsplucous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. ~ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a briste brush or scouring pad. Vite expression. ~ Use a soft, dampened sponge or cloth to clean. Never use abrasive m					
Tap Hole And Outlet Hole Dimension Internal diameter of outlet hole dia. Ø45 +2/-1 mm Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole ≤ 200 mm Product Features Rectangular counter top Basin Tap hole and over flow hole Anti germ glaze Accessones incluben Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUIDELINES Installation Template and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. ¬ Vitreous china sanitary ware Iroducts are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed. Carefully inspect the new product for damage before installation. ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. ¬ Nike void cleanners to sit or soak on the product. ¬ Jo no tallow cleaners to sit or soak on the product. ¬ Use soft, dampened sponge or lot to clean. Never use abraisive material like a briste brush or scouring pad. ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners. ¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface im	Outlet				
Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole s 200 mm Product Features Rectangular counter top Basin Fap hole and over 100w hole Anti germ glaze Accessonies INCLUDED Installation Template Overflow hole Cap Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUDELINES - Vitreous china sanitary ware products or fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. - The product is heavy and it is recommended that two persons hold it while it is being fixed. - Carefully inspect the new product for damage before installation. - Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. - Nisk of sternal leakage. Do not lift or rock the bowl after placement. - Always test your cleaning solution or an inconspicuous area on the product before applying it to the entire surface. - Ob on allow cleaners to sit or saco on the product. - Use a soft, dampened sponge or club to clean. Never use alrasive material like a bristle brush or scouring pad. - Wire warfaces clean and rines completely with water immediately after applying cleaners. - Clean Chrome, stainless steel surfaces one a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent					
Rectangular counter top Basin Ap hole and over flow hole Anti germ glaze ACCESSORIES INCLUDED Template Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUIDELINES					
Product Features Tap hole and over flow hole Antigerm glaze Antigerm glaze Accessones included Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUIDELINES Installation and use of the solid personal injury) at all times during its storage, handling, installation and use thereafter. ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed. - ¬ Carefully inspect the new product for damage before installation. - ¬ Risk of product damage. Over tighterning may cause breakage or chipping of vitreous china. - ¬ Risk of stermal leakage. Do not lift or rock the bowl after placement. - ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. - > Do not allow cleaners to sit or soak on the product. - ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. - ¬ Wipe surfaces clean and rinse complexes, use only warm water to clean and then dry with a soft cloth. - QUALITY MANAGEMENTSKIN Sont all concases the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions area in mark (finderane 2 s MM), Jaquar reserves the right to make the encessary amendments at any time without prior notice.					
Anti germ glaze Accessories included Accessories included Template Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUDELINES - Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereadre. - Vitreous china sanitary ware product is neavy and it is recommended that two persons hold it while it is being fixed. - Carefully inspect the new product for damage before installation. - Risk of product damage. Over tightering may cause breakage or chipping of vitreous china. - Nike of external leakage. Do not lift or rock the bowl after placement. - Always test your cleaning solution or an inconsplicuous area on the product before applying it to the entire surface. - O not allow cleaners to sit or solution or an inconsplicuous area on the product before applying deaners. - Clean Chrome, stainless steel surface sonce a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately after applying cleaners. - Quality MANAGEMENT SYSTEM - USE ON The product support on the product before applying cleaners. - Clean Chrome, stainless steel surface sonce a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. - Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. Out of the surface sond on the surface information presented subject to changes due to requirements in different sites, markets and/ or countries.	Product Features				
Template Installation Template Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUIDELINES					
Overflow hole Cap ZPS-WHT-9012B CARE AND CLEANING GUIDELINES - Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. The product is heavy and it is recommended that two persons hold it while it is being fixed. Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. - Wherever chrome plating is used on the product, use only warm water to clean and then dry with a soft cloth. OUALITY MANAGEMENT VSTEM - ISO 901 DiSCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm. (Toleranc	ACCESSORIES INCLUDED				
CARE AND CLEANING GUIDELINES Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. The product is heavy and it is recommended that two persons hold it while it is being fixed. Carefully inspect the new product for damage before installation. Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	Template	Installation Template			
Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter. Vitreous china sanitary ware product is neavy and it is recommended that two persons hold it while it is being fixed. Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. Vies surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	Overflow hole Cap	ZPS-WHT-9012B			
thereafter. The product is heavy and it is recommended that two persons hold it while it is being fixed. Carefully inspect the new product for damage before installation. Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of product damage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001	CARE AND CLEANING GUIDELINES				
Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. Do not allow cleaners to sit or soak on the product. Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.				
	¬ Carefully inspect the new product for damage before installation.				
	¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.				
- Do not allow cleaners to sit or soak on the product Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad Wipe surfaces clean and rinse completely with water immediately after applying cleaners Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	¬ Risk of external leakage. Do not lift or rock the bowl after placement.				
- Do not allow cleaners to sit or soak on the product Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad Wipe surfaces clean and rinse completely with water immediately after applying cleaners Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product					
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	¬ Do not allow cleaners to sit or soak on the product.				
Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.				
¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. QUALITY MANAGEMENT SYSTEM - ISO 9001 Image: Comparison of the product of	¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.				
QUALITY MANAGEMENT SYSTEM - ISO 9001 DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.				
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.				
are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	QUALITY MANAGEMENT SYSTEM - IS	SO 9001			
	are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.				
		Checked by	Approve	ed by	